

5 Clean Revised first full paragraph of Page 11 of the
6 specification, beginning on line 4 and ending at line 26:

A2
4 An alternate embodiment of the invention is shown in
5 Figure 4A wherein the cover sheets 64A are cut with
6 openings 80A to receive six photographs per page set,
7 three on each face of each page, on opposite sides of
8 the fold line 80B. Figures 4B, 4C and 4D illustrate
9 alternate constructions of the cover sheets 64B, 64C and
10 64D. In the Figure 4B embodiment, the cover sheet 64B
11 has six openings 80E on each side of the fold line 66B.
12 Four horizontal glue lines 70B are above and below each
13 opening. Insertion and removal of photographs is
14 facilitated by vertical slots 84B between the laterally
15 spaced openings of each face of each page. The Figure 4C
16 embodiment is cut to form three landscape oriented
17 openings 80C on each side of the centerline 66C with glue
18 lines 70C above and below, and with two portrait oriented
19 openings laterally spaced therefrom. A horizontal slot
20 84C is located between the portrait oriented openings on
21 each side for picture insertion and/or removal. The
22 embodiment of Figure 4D features openings 80D of various
23 sizes and orientations on each side of the fold line 66D.
24 Glue lines 70D are vertically positioned on opposite
25 sides of the openings with slots 84D adjacent to each
26 opening 80D for picture insertion and/or removal.